



500 SERIES - FC 1124

AT AIR 4990



SAFETY FEATURES

Active Safety Features

Vehicle Stability Control (VSC) Equipped

Anti-lock Brake System (ABS) Equipped

Pre-Collision System (PCS) Equipped

Pre-Collision System (PCS) is inclusive of
 Safety Eye (SE)
 Autonomous Emergency Braking (AEB)
 Pedestrian Detection (PD)

Traction Control (TC) Equipped

Lane Departure Warning System (LDWS) Equipped

Staggering Warning (SW) Equipped

Adaptive Cruise Control (ACC) Equipped

Reverse Camera (RC) Equipped

Passive Safety Features

SRS airbag for driver Equipped

SRS Seat belt pretensioner for driver Equipped

Front Underrun Protection device (FUPD) Equipped

ECE-R29 Cab Strength Certified Equipped

pPNLT EMISSION LEVELS (EURO 6 EQUIVALENT) 4 X 2 CAB CHASSIS

*Illustration may contain items not standard to the model

KEY SPECIFICATIONS

GVM 11,000kg

GCM 20,000kg

Power 240hp/177kW

Torque 794Nm Torque

Transmissions 6 speed Automatic

ENGINE & DRIVELINE SPECIFICATIONS

500 SERIES - FC 1124
AT AIR 4990

ENGINE	
Model	Hino A05C-TE
Max. output (ISO NET)	240hp/177kW @ 2,300RPM
Max. torque (ISO NET)	794Nm @ 1,400RPM
Max. engine RPM	2,550RPM
Engine compliance	ADR 80/03 using Japan pPNLT
Type	Diesel, turbocharged & intercooled 4 cylinder with overhead camshaft
Combustion system	Direct injection with EGR
Bore & stroke	112 x 130mm
Piston displacement	5.123L
Compression ratio	17.0:1
Fuel injection	Electronic control common rail
Air compressor / bore & stroke	Single cylinder / 70 x 40mm
Air cleaner	Dual paper elements
Exhaust	Horizontal outlet RHS
Emission Control System	DPR & SCR (AdBlue®)
Engine Immobiliser	Equipped

SUSPENSION & LOAD LIMITS		
Front	Front axle model	LF 456
	Front axle type	I-Beam, reverse elliot
	Suspension	Taper leaf springs with shock absorbers and stabiliser
	Spring Dimensions	1,300 x 70mm
	Number	3
	Spring rate (kgf / mm2)	23
	Axle limit (including suspension)	4,100kg
Rear	Tyre limit	4,000kg
	Rear axle model	SH13
	Rear axle type	Fully floating, single reduction by hypoid gears
	Rear suspension types	Air
	Suspension description	Hendrickson HAS 200 with shock absorbers and mechanical ride height valve
	Axle limit (including suspension)	7,000kg
	Tyre limit	7,600kg

FUEL TANK	
Material	Steel
Fuel capacity	200L
Lockable fuel cap	Equipped
Prefilter & sedimenter	Equipped
Adblue® capacity	19L

BRAKES	
Type	Drum brakes front and rear
Control	Air Over Hydraulic (AOH), Dual circuit
Drum diameter x lining width front	320 x 110mm
Drum diameter x lining width rear	320 x 120mm
Air Dryer	Equipped
Vehicle Stability Control (VSC)	Equipped
Pre-Collision System (PCS)	Equipped
Anti-lock Brake System (ABS)	Equipped
Traction Control (TC)	Equipped
Park brake	Spring brake acting on rear wheels
Exhaust & engine brake (Jake Brake)	Equipped
Brake lock	Equipped

WHEELS & TYRES	
Wheel type	6 stud disc wheel (JIS type) PCD 222.25
Rim size	6.75 x 17.5 with 135 mm offset (alloy)
Tyre size	235/75R17.5 132/130
Number of tyres	7 including the spare
Spare tyre carrier	Equipped

TRANSMISSION & GEAR RATIOS		
Make and description	Allison 2500, 6 speed with Hino T-bar cable shift and MID gear display	
Type	Double overdrive	
Gear Ratios	1	3.512
	2	1.896
	3	1.439
	4	1
	5	0.737
	6	0.643
	Reverse	5.085
Torque convertor & ratio, TC222	1.58	
Rear axle ratio	4.333	
PTO option/Torque capacity	Dual/339Nm	

PERFORMANCE	
Calculations based on 11t GVM with 235/75R17.5 tyres	
Engine RPM @ 100km/h	1,922
Max theoretical speed (km/h)	134
Gradeability tan (%) @ GVM	45.5

CAB, INSTRUMENTATION & CHASSIS

500 SERIES - FC 1124
AT AIR 4990

CAB DETAILS

Type	Forward control, day cab, all steel construction with torsion bar tilt mechanism
Grille colour	Matte Grey
Seating capacity	3
Drivers seat	ISRI 6860 NTS2 air suspension, 10 way adjustable with integrated safety belt and rear pocket
Side passenger seat	High back and reclining seat
Centre seat	Foldaway type with integrated tray
Seat belts	3 point lap sash for driver and side passenger, 2 point lap for centre position
Sunvisor and overhead console	For driver and passenger sides
Windscreen wipers	2 arm wiper and washers, 2 speed with intermittent
Cab heater and air conditioner	Equipped with 4 speed fan
Rear view mirrors	External : Electric & heated, 2 flat type, 2 convex spotters & kerb view
Auxiliary power supply	12 volt 120W socket and USB 2.1 amp
Floor covering	Vinyl type
Central locking and keyless entry	Equipped with immobiliser
Cab storage pockets	Equipped in both side doors
Power windows	Equipped
Foot rest	Equipped
Cup holders	3 centre and 2 door beverage holders
Multimedia System	6.5" LCD, HD touch screen display with DAB+ AM/FM radio, AUX input, Bluetooth®4.1, Android 6.0,CANBUS connected and Wi-Fi enabled

STEERING

Type	Telescopic and tilt steering column with locking device. Recirculating ball with integral power steering.
Gear ratio	19.0:1
Steering angles - Inside	53°
Steering angles - Outside	38°

CHASSIS FRAME

Main section in mm (depth x flange x thickness)	228.4 x 73 x 5.2
Chassis width	820mm
Tensile strength	540 N/mm ² (55 kgf/mm ²)
Front Underrun Protection Device (FUPD)	Equipped
Tow hook capacity (front and rear)	2,000 kgf (max angle of 15°)
Type	Ladder-shaped channel section side rails


INSTRUMENTATION

Metres	Steering wheel controls
Speedometer	Cruise control
Tachometer	MID controls
Air Gauges	Additional switches and controls
LCD display	External flat mirror control
Time	VSC off
Temperature Gauge	PCS off
Adblue® Gauge	LDWS off
Fuel Gauge	Idle up
Odometer	Quick warm up
Hour Meter	Mirror heater
Date & Day	Engine brake
Multi Information Display (MID)	System Check
General information	Power and economy
Cruise Control setting	DPR regeneration
Eco Tree	Electric window lock out
Display setting	Head light leveller
Safe driving settings	Gear position

ELECTRICAL

Type	24 volt negative earth
Batteries	12 volt x 2 120AH (115F51)
Alternator capacity	24 volt x 90 amp
Starter type	24 volt x 4.5kW
Headlamps	LED main beam with LED daytime running lamps
LED cornering/Fog lamps	Equipped
LED Interior and reading lamp	Equipped
Electric air horn	Equipped
CANBUS connected	Equipped J1939 protocol (see BMM for details)


POWER & TORQUE CHART (ISO NET) A05C-TE



DIMENSIONS	
Suspension	Air
Wheel base (WB)	4,990
Max Nominal Body Length	7.7m
Product Code	FC2AL1G-DXAAE
OL	8,435
OW	2,190
OH	2,440
CA	4,355
FOH	1,145
ROH	2,260
RCH (at axle)	780
FT	1,780
RT	1,660
Kerb to Kerb	15,600
Wall to Wall	17,000

Indicative Chassis Mass – kg (10 litres of fuel, no tools or spare tyre & subject to a ±3% tolerance)

Total	3,515
Front	2,405
Rear	1,110
GVM	11,000
GCM	20,000



Drawings are for reference only to the table. For specific chassis layouts and dimensions please refer to Body Mounting Manual drawings.

WARRANTY			
Medium Duty Model	Axle configuration	Standard warranty (whichever comes first)	Engine & Powerlines (whichever comes first)
FC 1124	4 x 2	24 months or 100,000kms	36 months or 150,000kms

DISCLAIMER

Important notice. Hino Trucks are distributed in New Zealand by Hino Distributors (NZ) Ltd.

All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Distributors (NZ) Ltd reserves the right to alter any details of the specifications and equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features and options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices and availability.